



**MULTILUMEN  
SELECTOR**

**EASY 5 COLORS  
SELECCTOR**  
2700K • 3000K • 3500K • 4000K • 5000K




## TRIM INSERTS OPTIONS

### BAFFLES



REL537-BT-SN-SN



REL537-BT-P-BK



REL537-BT-DBZ-DBZ

### REFLECTORS



REL537-RT-CL-WH




REL537-RT-DBZ-DBZ



REL537-RT-P-BK



REL537-RT-SN-SN



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
950	981	11W
1100	1170	14W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%



## INSTALLATION

Elite LED Retrofits come standard with quick connectors ready for installation in Elite Lighting's LD series recessed housing that are Energy Star and Title 24 rated (LD4IC-AT, LD5IC, LD6IC-AT).

You MUST seal all gaps between the ceiling and fixture with weatherproof silicone sealant. This deters moisture and water from damaging fixtures and other mechanical ceiling elements.

## FEATURES

Elite REL Retrofits are ideal for new construction or remodel applications when paired with an Elite recessed housing. Engineered for quick and easy retrofitting into existing incandescent recessed housings. An easy 5-Color SeleCCTor switch allows the contractor to easily switch between 5 different color temperatures in the field. Multiple trim types, trim finishes, and apertures make the REL Retrofits perfect for hotels and restaurants, assisted living facilities, dormitories, and kitchens.

LUMENS	950/1100
CCT	27K/30K/35K/40K/50K
CRI	90+
COLOR QUALITY	3 Step MacAdam Ellipses
TRIM	Baffle, Aluminum die-cast body and trim
REFLECTOR COLORS	WH (White), BK (Black)
FLANGE COLORS	W (White), P (Black)
DIMMING	DIMTR (Triac)+DIM10 (0-10V Dimming)
LIFETIME	50,000 Hours
EMERGENCY	16W high voltage inverter ( Installed into the housing)*
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21

\* Consult Factory

## EASY 5-COLOR SELECCTOR SWITCH

Easy 5-Color SeleCCTor switch can be adjusted to a choice of 5 different Kelvin color temperatures in the field. Options include 27K/30K/35K/40K/50K. The SeleCCTor switch is located on the junction box for easy adjustment before and after installation. The SeleCCTor switch is easily accessible by lowering the luminaire from the opening.

### CONSTRUCTION

Die-cast aluminum body for maximum heat dissipation. Baffle and reflector trims are available.

### OPTICS

A 55-degree cutoff angle delivers glare-free, even illumination.

### COMPATIBLE WITH ELITE 6" HOUSINGS

The Elite REL637 series works in Elite housings (LD4IC-AT, LD5IC, LD6IC-AT) and existing 6" incandescent housings. Elite LED Retrofits are shipped with a medium-based socket adapter to allow installation into housings with an E26 incandescent medium-based socket. Also suitable for use in most 6" and 5" incandescent recessed downlight housings.

### QUICK AND EASY INSTALLATION

Quick connectors for use with 5" or 6" housing or Edison base adapter for retrofitting into existing 6" incandescent housings.

Torsion springs pre-installed onto both sides of fixture, installing easily in most 6" incandescent downlights.

Insert torsion springs into can and press trim to ceiling. Friction blades are also included.

### APPLICATIONS

Damp and wet-location-rated ideal for indoor and outdoor use, shower, and other wet-location applications. IC-Rated and Air Tight and may be installed in direct contact with insulation.

### DRIVER ELECTRICAL INFORMATION

Driver is rated for 50 to 60Hz at 120V/277V input, produces less than 20% THD, has a power factor between 90% and 100%, and is thermally protected for additional safety.

### DIMMING & DRIVER INFORMATION

DIMTR - Triac & electronic low voltage (DIMTR-120) flicker-free dimming. Available in 120V. Dimmable down to 5% of initial lumens, standard.

### WARRANTY

Five-year warranty for parts and components. (Labor not included)

### LISTINGS

Energy Star  
cETLus  
Title 24  
JA8E  
RoHS  
IECC  
New York State

EXAMPLE: REL537-950L/1200L-DIMTR/120-DIM10/MVOLT-27K/30K/35K/40K/50K-90-W-WH

TYPE	LUMEN	CCT	CRI	FINISH
REL537	<input type="checkbox"/> 950L/1100LDIMTR/120-DIM10/MVOLT	<input type="checkbox"/> 27K/30K/35K/40K/50K	<input type="checkbox"/> 90+	<input type="checkbox"/> W-WH-White <input type="checkbox"/> P-BK-Black

TRIM RING ACCESSORY: REL537-BT-SN-SN

BT - BAFFLE	RT - Reflecto
<input type="checkbox"/> REL537-BT-SN-SN <input type="checkbox"/> REL537-BT-P-BK <input type="checkbox"/> REL537-BT-DBZ-DBZ	<input type="checkbox"/> REL537-RT-CL-WH <input type="checkbox"/> REL537-RT-DBZ-DBZ <input type="checkbox"/> REL537-RT-P-BK <input type="checkbox"/> REL537-RT-SN-SN





\*Trim accessories order separate

ACCESSORY: GU24SA

OPTIONS
<input type="checkbox"/> GU24SA - SOCKET FOR LED RETROFIT TO GU24

\*Accessories order separate

EXAMPLE: HLD5IC-AT

COMPATIBLE ELITE LIGHTING HOUSINGS			
 <b>IC RATED</b>		 <b>IC RATED</b>	
<input type="checkbox"/> LD5IC	<input type="checkbox"/> LD5-AT	<input type="checkbox"/> LD5RIC-AT	<input type="checkbox"/> LD5R-AT
<input type="checkbox"/> HLD5IC-AT	<input type="checkbox"/> HLD5-AT	<input type="checkbox"/> HLD5RIC-AT	<input type="checkbox"/> HLD5R-AT
<input type="checkbox"/> LD500IC-AT	<input type="checkbox"/> B5-AT	<input type="checkbox"/> EZ5IC-AT	<input type="checkbox"/> B5R-AT
<input type="checkbox"/> EZ5IC-AT		<input type="checkbox"/> B5RIC-AT	
<input type="checkbox"/> B5IC-AT			
<input type="checkbox"/> B5IC-100-AT			
<input type="checkbox"/> B500-IC			

\*Housing order separate