






EASY 5 COLORS SELECTOR SELECTOR


RING COLORS





Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

MOUNTING



FEATURES

The Elite LED Slim Surface Mount has been engineered to install into most standard junction boxes. Up to 1000 usable lumens are directed from the luminaire to the work surface. Easy to install, applicable to junction box or recessed can installation.

LUMENS	800/1000L	
ССТ	27K/30K/35K/40K/50K	
CRI	90+	
COLOR QUALITY	3-Step MacAdam Ellipse	
DIMMING	DIMTR (Triac Dimming), DIM10 (0-10V Dimming)	
FINISH	WH (White), BK (Black), BZ (Bronze), SN (Satin Nickel)	
LIFETIME	50,000 Hours	

OPTICS

The Elite LED Module system is much more than just a simple LED retrofit. The Elite LED system is a highly engineered work of design and optical science which produces up to 1000 lumens. Our meticulously crafted optics gather the light scattered by the LED chip and shape it into a functional beam with uniform light distribution.

DIMMING

Intended for Triac(120V) and 0-10V dimming (120-277V) based on configuration. Minimum 90°C supply conductors.

COMPLIANCE

Non-conductive fixture for shower light application. Product complies with the requirements of the California Energy Commission regulated under Title 24.

LISTING

ETL listed Energy Star certified

WARRANTY

The Elite LED lighting system carries a five-year carefree warranty for parts and components. (Labor not included)

EXAMPLE: RL791-800L/1000L-DIMTR/120-DIM10/MV0LT-27K/30K/35K/40K/50K-90-WH

TYPE	LUMEN	CCT	CRI	FINISH
RL791	B00L/1000L-DIMTR/120-DIM10/MV0LT	27K/30K/35K/40K/50K	D 90+	UH-White (standard)
				RL791-RT-5CCT-BK-Black
				RL791-RT-5CCT-BZ-Bronze
				RL791-RT-5CCT-SN-Satin Nickel





Due to the changes of constant improvement in LED technology, all details are subject to change without notice. Consult factory for up to date information. 08122021