



**MULTI LUMEN
SELECTOR**

**EASY 5 COLORS
SELECTOR**
2700K • 3000K • 3500K • 4000K • 5000K



RING COLORS




Black



Satin Nickel



Bronze



11/16" 1-1/2"

NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
1300	1300	14W
1000	1000	11W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

INSTALLATION

You MUST seal all gaps between the ceiling and fixture with weatherproof silicone sealant. This deters moisture and water from damaging fixtures and other mechanical ceiling elements.

MOUNTING



4" Square
(Plastic)



4" Octagonal
(Metal)



4" Square
(Metal)



Fire Rated
J-Box

Note: recommended junction box

FEATURES

The Elite LED Slim Surface Mount has been engineered to install into most standard junction boxes. Up to 1300 usable lumens are directed from the luminaire to the work surface. Easy to install, applicable to junction box or recessed can installation.

LUMENS	1000/1300L
CCT	27K/30K/35K/40K/50K
CRI	90+
COLOR QUALITY	3-Step MacAdam Ellipse
DIMMING	DIMTR (Triac Dimming), DIM10 (0-10V Dimming)
FINISH	WH (White), BK (Black), BZ (Bronze), SN (Satin Nickel)
LIFETIME	50,000 Hours

OPTICS

The Elite LED Module system is much more than just a simple LED retrofit. The Elite LED system is a highly engineered work of design and optical science which produces up to 1300 lumens. Our meticulously crafted optics gather the light scattered by the LED chip and shape it into a functional beam with uniform light distribution.

DIMMING

Intended for Triac(120V) and 0-10V dimming (120-277V) based on configuration. Minimum 90°C supply conductors.

COMPLIANCE

Non-conductive fixture for shower light application. Product complies with the requirements of the California Energy Commission regulated under Title 24.

LISTING

ETL listed

Energy Star certified

WARRANTY

The Elite LED lighting system carries a five-year carefree warranty for parts and components. (Labor not included)

EXAMPLE: **RL991-1000L/1300L-DIMTR/120-DIM10/MVOLT-27K/30K/35K/40K/50K-90-WH**

TYPE	LUMEN	CCT	CRI	FINISH
RL991	1000L/1300L-DIMTR/120-DIM10/MVOLT	27K/30K/35K/40K/50K	90+	<input type="checkbox"/> WH-White (standard) <input type="checkbox"/> RL991-RT-5CCT-BK-Black <input type="checkbox"/> RL991-RT-5CCT-BZ-Bronze <input type="checkbox"/> RL991-RT-5CCT-SN-Satin Nickel