


FEATURES

Enhance the aesthetic appeal of your bathroom, dressing room, or bedroom with the Rounded Smart LED Mirror. This stylish and sophisticated mirror not only elevates your space but also provides a personalized lighting experience. The integrated smart features, including dual-touch sensors—one for controlling the light and another for the anti-fog function—allow you to customize your lighting experience effortlessly.

The highlight of this mirror is its adjustable CCT color functionality and its smart defogger function. Choose from a range of color temperatures, from warm to cool, to create the ideal ambiance for any occasion. Say goodbye to traditional switches and embrace the convenience of modern living.

FUNCTION OPTIONS




OPTIONAL FUNCTION



Touch Sensor

SENSOR



TECHNICAL DETAILS

LUMENS	1400L, 1800L, 2100L, 2600
CCT	3000K/4000K/6500K
CRI	>80/>90
INPUT	120V
POWER	24W, 36W, 42W, 53W
SIZE	Ø24", Ø28", Ø32", Ø39"

MOUNTING	Wall Mount
IP RATING	IP44
RING COLOR	BK-Black, GD-Golden, CR-Chrome, C_-Custom
DIMMING	Dimmable <small>Dimming is integrated into the mirror; no separate dimmer, or control required.</small>
LIFE TIME	L70 at 30,000 Hours
MATERIAL	Glass+Aluminum+PC



MAINTENANCE

Use a soft, lint-free cloth or microfiber cloth to gently wipe the surface of the mirror. If necessary, lightly dampen the cloth with water or a mild glass cleaner specifically designed for mirrors. Never use abrasive materials like rough sponges, scrub brushes, or abrasive powders on the mirror. They can scratch or damage the mirror's surface and coating.

OPTICAL SYSTEM

LED frame design provides exceptional light distribution. Illumination is spread around the surface emitting soft, even light.

CONSTRUCTION

Crystal-clear reflection with a combination of blend of glass, aluminum, and PC (polycarbonate). To ensure both strength and versatility, the mirror incorporates PC (polycarbonate) into its construction. PC is known for its impact resistance, making the mirror more resilient to accidental bumps or drops. This material also contributes to the lightweight nature of the mirror, allowing for easy installation and handling.

MOUNTING



Easy to install, the Rounded Smart LED Mirror comes equipped with a bracket for mounting, making installation a breeze. The bracket ensures secure and hassle-free mounting, allowing for versatile placement and seamless integration into any space

OPTIONS

Optional ring in Black, Golden, Chrome color or Custom RAL.

SENSOR

Dual-touch sensors, one for controlling the light and another for the anti-fog function. The anti-fog film can be independently controlled via its sensor.

	Short-touch the switch for on/off functionality. Double-click the switch to cycle through color temperature options: 3000K, 4000K, and 6500K. Long-touch the switch for dimming control. The defogger film will operate in conjunction with the light and will automatically turn off after 1 hour. You can also control it through a dedicated button.
	Defogger, short touch for on/off of the defogger function, the defogger will be off automatically within 60 minutes without operation.

DRIVER ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 100-120V/220-240V.

DIMMING

Smart Touch Dimming, refer to diagram on page 1.

WARRANTY

Five-year (limited) warranty for parts and components. (Labor not included)

LISTINGS

RoHS Listed.
ETL Listed.
CE Listed.

VOICE COMMAND CONTROL

You Say	You Will See
Hello mirror / Mirror mirror	Voice control activate
Turn on the light/Light on	Light turns on
Turn off the light/Light off	Light turns off
White color/White light	White color (6500K)
Warm color/Warm light	Warm color (3000K)
Natural color/Natural light	Natural color (4000K)
Brighter	Brighten 20% each time
Dimmers	Darken 20% each time
Brightest	Highest brightness
Dimmest	Lowest brightness
Turn on Defoggers/Defoggers on	Defoggers start working (they will turn off automatically within 60 minutes)
Turn off Defoggers/Defoggers off	Defoggers stop working

After the voice is active, you can issue commands to it continuously instead of activating it once per command. **The maximum interval for each command is 15 seconds.** If it exceeds 15 seconds, the voice control will be automatically closed after prompting.

Example: SMR2-LED-RD-24-1400-120-30K/40K/65K-80/90-BK-SM

SMR2-LED-RD									
SERIES	LUMINAIRE SIZE	LUMENS	VOLTAGE	CCT	CRI	RING COLOR	MOUNTING	OPTION	
SMR2-LED-RD	24 - Ø24" 28 - Ø28" 32 - Ø32" 39 - Ø39"	1400 - 1400L 1800 - 1800L 2100 - 2100L 2600 - 2650L	120 - 120V	30K/40K/65K - 3000K/4000K/6500K	80/90 - >80/ >90	BK - Black GD - Golden CR - Chrome C_ - Custom	WM - Wall Mount	VC - Voice Control	