

ST801-AL



ST802-AL

APPLICATION: For concrete use only

BODY: Galvanized steel

FACE PLATE: High-grade die-cast aluminum

Supplied standard with two 3/4" knockouts located on sides.

GASKET: Single piece molded silicon for wet location

LENS: Frosted tempered glass

FINISH: Bronze thermoset powder coat

EXTERNAL LOUVER: Anodized 45" cut-off louver

REFLECTOR: High performance aluminum reflector assembly for superb light output.


INSTALLATION: Two 1/2" NPS wiring holes

Feed through listed

BALLAST: Thermally protected, current controlled ballast, will produce full light output, increase lamp LIFE with no noise or flicker.

LISTING:

UL/ cUL for wet locations.



Ordering Example: ST8BX-LED-WW-12V-ST801-WH

HOUSING	FACE PLATE	FINISH
ST8BX-LED-WW-12V*	ST801	WH- WHITE
ST8BX-LED-CW-12V*	ST802	BZ- BRONZE
ST8BX-LED-WW-120V		AL- SATIN ALUMINUM
ST8BX-LED-CW-120V		

***MUST BE USED WITH REMOTE DRIVER**

ST7BX LED EXTERIOR STEP LIGHTS SERIES



ST701-BR



ST702-BR



ST703-BR

APPLICATION: For concrete use only

BODY: High grade die-cast aluminum with 0.3% Copper to prevent corrosion in concrete applications.

Supplied standard with three 3/4" NPS holes located on top, side & back.

FACE PLATE: High-grade die-cast aluminum

GASKET: Single piece molded silicon for wet location

LENS: Frosted tempered glass

EXTERNAL LOUVER: Anodized 45" cut-off louver


REFLECTOR: High performance aluminum reflector assembly for superb light output.

INSTALLATION: Two 1/2" NPS wiring holes Feed through listed

BALLAST: Thermally protected, current controlled ballast, will produce full light output, increase lamp life with no noise or flicker.

LISTING:

UL/ cUL for wet locations.



Ordering Example: ST7BX-LED-WW-12V-ST701-WH

HOUSING	FACE PLATE	FINISH
ST7BX-LED-WW-12V*	ST701	WH- WHITE
ST7BX-LED-CW-12V*	ST702	BZ- BRONZE
ST7BX-LED-WW-120V	ST703	SN- SATIN NICKEL
ST7BX-LED-CW-120V		AL- SATIN ALUMINUM

***MUST BE USED WITH REMOTE DRIVER**

LED STEP LIGHT